

DECLARATION OF PERFORMANCE (DoP)

according to Construction Products Regulation (CPR) No 305/2011

DoPNo. 09/0001 - en

- 1. Unique identification code of the product-type: Insulation fastener IPD 8
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-09/0001, annex 3 Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Generic type	Plastic anchor with steel nail			
For use in	External thermal insulation composite systems in concrete and masonry covered sizes: IPD 8			
Option / Category	a, b, c, d, e			
Loading	Static and quasi-static			
Material	Plug: <u>Polypropylene:</u> covered sizes: IPD 8 Nail: <u>Zinc-plated steel with polyamide PA6 covered head:</u> covered sizes: IPD 8			
Temperature range if applicable	-40°C - +40°C			

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

KLIMAS Wkręt-Met Sp. z o.o. Sp. komandytowa ul. Wincentego Witosa 170/176 Kuźnica Kiedrzyńska 42-233 Mykanów

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): --
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: system 2+
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: --
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Institut für Bautechnik (ITB), Warschau

issued: ETA-09/0001

on the basis of ETAG 014

The notified body 1488 performed under system 2+:

- initial inspection of factory and of factory production control,
- continuous surveillance, assessment and approval of factory production control.

9. Declared performance:

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
Characteristic resistance for tension	ETAG 014	ETA-07/0337, Annex 5	ETAG 014
Characteristic resistance for shear	-	-	
Minimum spacing and minimum edge distance	ETAG 014	ETA-07/0337, Annex 4	
Displacement for serviceability limit state	-	-	

Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies: --

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Achim Ruppertz Marketing and Technical Manager

Aichach, 26.6.2013

